



SALINITY CELL CATALOGUE #: MC-163

GENERAL DESCRIPTION:

The McNab MC-163 salinity cell is an in-line water quality sensor used in conjunction with Navy monitoring instruments. The TFE surfaces function to minimize galvanic voltages and action between the noble metal electrodes and non-noble metal valve/fittings and cell housing.

APPLICATION:

The MC-163 salinity cell is primarily used to monitor water quality in distiller evaporators and feed and condensate systems.

SPECIFICATIONS:

Pressure:	150 psi
Temperature:	Full temperature compensation to 360 degrees F.
Cable:	6 ft. cable supplied with each cell.
Installation:	Designed to fit with NPT threads 1"
Weight (typ):	2 Lbs.
System:	80 volts max.
Test:	Cell test module
Length:	5" overall (approx.)
Diameter:	Body, 1 5/16" (approx.)
Material:	Body, Brass



NOTES:

- 1- Unless specified, parts to be considered as listed, "or equivalent."
 - 2- Specifications subject to change without notice.
-

McNAB, INCORPORATED

20 North MacQuesten Parkway ♦ Mount Vernon, NY 10550 USA

Phone: 914-699-1616 ♦ Fax: 914-699-1671

Web: www.themcnab.com ♦ E-mail: info@themcnab.com